

Santa Stocking

Sew stocking front, back and lining at the same time

Fabric and supplies:

Outer fabric: Minimum 10" x 16" for stocking

Lining: Minimum 10" x 16"

Contrasting Cuff: minimum 6" x 18"

Option 1 – Using the AccuQuilt cutter and die.

Using the AccuQuilt Santa Stocking die, cut 2 layers of outer fabric (right sides facing) and two layers of lining (right sides together, face to face). Place fabrics only on the sock part of the die.

Cut 2 pieces of cuff fabric on the cuff portion of the die

NOTE: You can cut two layers of outer fabric and 2 layers of lining, right sides facing, with one set on top of the other.

DO NOT CUT MORE THAN 4 LAYERS OF FABRIC AT A TIME.*

Assemble the Stocking

Both Options

1. Lay stocking front & back right sides together on top of lining front and back, right sides together. Using a ¼" seam, sew through all 4 layers at the same time, leaving tops open. (Fig. 1). Clip
2. Insert hand into stocking fabric. Grab the toes of **both** the fabric and the lining. Turn right side out. (Fig 2). The lining should be on the inside and the outer fabric on the outside - where it is supposed to be.
3. Press and trim top edge if necessary.



Fig 1



Fig. 2

Hanging Loop

1. From the fabric scraps cut a 2" x 6" rectangle.
2. Fold the rectangle in half lengthwise and press.
3. Open and fold each long side to the middle crease.
4. Fold on the crease and press.
5. Edge stitch along both edges.

Cuff

1. With right sides facing, sew the short ends using a ¼" seam. Press seams open.
2. Fold the cuff in half lengthwise, wrong sides together and press.
3. Pin the hanging loop inside the back seam of the stocking with raw edges together. The loop should be facing down, next to the lining.
4. Place the folded cuff **inside** the top edge of the stocking, matching seams and raw edges. Pin and sew all around the edge using a ¼" seam, making sure to catch the loop between the lining and the cuff.
5. Turn cuff to outside and press. Top stitch ½" from top if desired.

Option 2 – Using the paper pattern.

1. Trace the stocking onto the paper side of a piece of wax coated freezer paper. **
2. Layer 2 pieces of the outer fabric, right sides together, and 2 pieces of the lining fabric, right sides together.
3. Press the freezer paper template on the right side of one of the outer fabric pieces. Pin all layers together.
4. Cut out on the drawn line, cutting through all four layers. (The seam allowance is included in the drawing.) If the fabric slips when cutting, cut just two pieces at a time instead of all four.
5. Remove the freezer paper template, keeping all fabric layers together.
6. Sew all four layers together, all around the stocking, leaving the tops open.
7. Follow the Assembly and Cuff instructions above to complete the stocking.

*Although AccuQuilt says you can cut up to six layers of fabric, please cut only 4 layers if you are using a cutter that belongs to someone else.


Four layers means 4 layers of quilt quality cotton fabric, 2 layers of fused fabric, 2 layers of denim or drapery fabric

Using denim for stocking

If cutting denim, cut only 1 or 2 sayers at a time, depending on the thickness and firmness of the denim. Brand new denim fabric with lots of sizing equals 2 layers when using the cutter (in other words, cut ONE layer of new, stiff denim at a time).

Using fleece

Fleece is NOT recommended for the stocking. It does not cut well using the GO! and the fleece gets stuck in the die and will need to be cleaned out after every cut. HOWEVER, fleece may be used for the cuff if you cut the pieces by hand.



Sock Top

Join with Sock Toe at dotted line.



Sock Toe

Join with sock top at dotted line.